

r.LiNK-Interface

RL-CCC-LOG

**Interface for activation of
factory rear-view camera input
for BMW vehicles with
Professional CCC navigation systems
and factory PDC behind**

Harness with open ends - version only for connection to xxxLOGiC interfaces.

Contents

1. Prior to installation

- 1.1. Delivery contents
- 1.2. Check compatibility of vehicle and accessories

2. Installation

- 2.1. Assignment of the female 12pin connector of harness RLC-CX011
- 2.2. Coding of rear-view camera
 - 2.2.1. Reversing the coding of rear-view camera
- 2.3. Picture settings

3. Mode of operation

4. Specification

5. Technical Support

Legal Information

By law, watching moving pictures while driving is prohibited, the driver must not be distracted. We do not accept any liability for material damage or personal injury resulting, directly or indirectly, from installation or operation of this product. This product should only be used while standing or to display fixed menus or rear-view-camera video when the vehicle is moving, for example the MP3 menu for DVD upgrades.

Changes/updates of the vehicle's software can cause malfunctions of the interface. We offer free software-updates for our interfaces for one year after purchase. To receive a free update, the interface must be sent in at own cost. Labor cost for and other expenses involved with the software-updates will not be refunded.

1. Prior to installation

Read the manual prior to installation. Technical knowledge is necessary for installation. The place of installation must be free of moisture and away from heat sources.

1.1. Delivery contents

Take down the SW-version and HW-version of the interface boxes, and store this manual for support purposes.



1.2. Check compatibility of vehicle and accessories

Requirements

Vehicle ONLY! BMW X5 (E70), X6 (E71)

Navigation Professional CCC with factory PDC behind

Installed interface xxxLOGiC interface

Limitations

Factory-TV-tuner Optionally available Video switch-box SW-V2X1-MQS is necessary to connect.

Factory-PDC The picture of the after-market rear-view camera can only be displayed in full-screen mode. The optical PDC will not be displayed, the acoustical PDC is still available .

2. Installation

Switch off ignition and disconnect the vehicle's battery! If according to factory rules disconnecting the battery has to be avoided, it is usually sufficient to put the vehicle in sleep-mode. In case the sleep-mode does not show success, disconnect the battery with a resistor lead.

2.1. Assignment of the female 12-pin connector of harness RLC-CX011

Cable colour	Assignment
Pin 1 ● pink	+12V ACC (Output) max.1.5A
Pin 2 ● blue	CAN-LOW (Input)
Pin 6 ● red	+12V Permanent (Input)
Pin 8 ● yellow	CAN-HIGH (Input)
Pin 9 ● green	Reverse gear (Output) max. 1.5A
Pin 12 ● black	Ground

2.2. Coding of rear-view camera

Press button "menu" while in main menu of the CCC for 5 seconds to code the navigation to rear-view camera.

2.2.1. Reversing the coding of rear-view camera

The above described coding of rear-view camera can be reversed by pressing the button "menu" for 5 seconds while in main menu of the CCC.

2.3. Picture settings


For an acceptable display of the rear-view camera video the PDC function (optical) must be set to OFF and camera function set to ON in the submenu of the CCC.
(Menu: Settings > Vehicle tires > Shunting Help > Image combinations)

3. Mode of operation

After engaging the reverse gear the rear-view camera will be displayed on the monitor automatically. It remains on display until the vehicle reaches a speed of 20km / h. The rear view camera can also be switched on or off manually by the PDC button. Even if the video of the rear-view camera is visible, the acoustic warning signals of the factory parking sensors are active.

4. Specifications

Operation voltage	10.5 – 14.8V
Stand-by power drain	<1mA
Operation power drain	~50mA
Power consumption	0.07-40W
Temperature range	-30°C till +80°C
Weight	38g
Measurements (box only) W x H x D	71 x 22 x 50 mm



CE 12V DC

5. Technical Support

Caraudio-Systems Vertriebs GmbH
manufacturer/distribution
Rheinhorststr. 22
D-67071 Ludwigshafen am Rhein

phone +49 621 95344170
email support@caraudio-systems.de

Legal disclaimer: Mentioned company and trademarks, as well as product names/codes are registered trademarks ® of their corresponding legal owners.