

# OBD-MMI3G-R-01

## Rear-view camera OBD-coder for Audi MMI3G basic/high navigation systems

**ONLY for vehicles with factory park distance control**

OBD-MMI3G-R-01 – For one vehicle

### Delivery contents

*Take down the SW-version and  
HW-version of the interface boxes,  
and store this manual for support  
purposes.*

HW \_\_\_\_\_

SW \_\_\_\_\_



OBD-MMI3G-R-01

### Legal Information

Changes/updates of the vehicle's software can cause malfunctions of the interface. We offer free software-updates for our interfaces for one year after purchase. To receive a free update, the interface must be sent in at own cost. Labor cost for and other expenses involved with the software-updates will not be refunded.

### Check compatibility of vehicle and accessories

#### Requirements

Vehicle	Audi
Navigation	MMI3G basic/high

#### Limitations

**ONLY for vehicles with factory park distance control!**

## Installation

1. Locate OBD-port and remove cover
2. Turn on ignition
3. Wait until the head-unit has booted
4. Plug coder into OBD-port
5. Leave coder for about 15 seconds in OBD-port
6. Remove coder from the OBD-port

To reverse the coding repeat steps 2.-7.

**Note:** After the first use on a vehicle, the coder OBD-MMI3G-R-01 is personalized to this vehicle (head-unit) and can be used unlimited times to code or reverse coding on this vehicle.


## Technical Support

**Caraudio-Systems Vertriebs GmbH**  
*manufacturer/distribution*  
Rheinhorststr. 22  
D-67071 Ludwigshafen am Rhein

**NavLinkz GmbH**  
*corporate sales/tech dealer-support*  
Eurotec-Ring 45  
D-47445 Moers

phone +49 180 3 907050  
email [support@caraudio-systems.de](mailto:support@caraudio-systems.de)

**Legal disclaimer:** Mentioned company and trademarks, as well as product names/codes are registered trademarks ® of their corresponding legal owners.

CE  12V DC
---