


Mini front and rear-view camera

CI-CAM-E-B168

Delivery contents



Product features

- Mini ball camera NTSC with 2 housings (black)
- Housing 1: Cable-guided thread tube with counternut
- Housing 2: Screw or glue fixing
- Optional housing 3: Rubber ring for in-mount
- System cable with throughput wire, e.g. for reverse signal
- Horizontal mount-under and vertical mount-on possible (by rotating the ball)
- Mirroring can be switched off - suitable also as front camera
- Sensor type CMOS 1/4 inch HD low-light sensitive
- Bezel F1.2
- Minimum illumination 0.01Lux, 800 TV lines
- Angle H=168°, V=118°, D=188°
- Guide-lines width selectable between car or truck
- Guide-lines can be switched off
- Protection class IP69K
- Suitable for permanent operation (connection to ACC)
- Operating voltage +12/24V (6 ~ 28V)
- Current consumption 50mA
- Video connection RCA male connector
- System cable of camera 4pin 3V
- Diameter of camera connector 4.5mm
- Total cable length 8.70m
- Operating temperature range -30°C to +75°C
- Dimensions in housing 1 - 24.2 x 24.35 x 22mm (w x d x h)

Installation



- Video signal
- +12V Reverse signal
- Throughput
- Ground

Note: If the camera is powered by reverse gear lamp signal, we recommend to install a relay between the power supply of the reverse signal and the power supply of the camera, to ensure a stable and uninterrupted power supply and to avoid errors in the vehicle computer.

In case the isolation of the camera is harmed in the moisture section close to the camera, it is mandatory to repair the isolation. Otherwise the camera will inevitably become moist inside sooner or later.

Camera configuration (cut cable loops if required)


With guide-lines



Without guide-lines



Mirroring - rear-view camera



Mirroring - front camera




Guide-lines - car



Guide-lines - truck



Housing options



E13

03 12699

